

# **300 MHZ FAMILY**

300 MHZ WIRELESS TRANSMITTERS AND RECEIVERS



## **PRODUCT**

## **TECHNOLOGY**

## **CERTIFICATIONS**








Go to the product page

## **APPLICATIONS**





Wireless Actuators

Limited Mobility

## **TECHNICAL SPECIFICATIONS**

Frequency	300 MHz
Radio Control Type	Analog
Input Voltage	24 VAC / VDC
Operating Temperature	14 – 131 °F (-10 – 55 °C)
Setup	10 dip switch access code programming
Power	
10T300HHX	(1) 9-volt battery
10T300KEYCHAIN	(1) 12-volt battery
10T300MINIPB	(1) 12-volt battery
10T300PB	(1) 9-volt battery
Receiver Dimensions	
Without Flange	$4 \%_{10}$ " (L) × 3 $\%$ " (W) × 1 $\%$ " (H)
With Flange	$5 \frac{1}{5}$ " (L) × $3 \frac{1}{5}$ " (W) × $1 \frac{2}{5}$ " (H)
Norm Conformity	CE, FCC, IC

## **PRODUCT SERIES**



10R300 300 MHz Analog receiver



10T300HH 1-Button handheld





10T300HH4 4-Button handheld transmitter



10T300KEYCHAIN 1-Button keychain transmitter



1-Button miniature wired transmitter



no case



DISCLAIMER Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.



